

SAFETY DATA SHEET



4195 Baja Beije Direct-To-Concrete A-Component

Section 1. Identification

GHS product identifier : 4195 Baja Beije Direct-To-Concrete A-Component : Not

Product code : available.

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Pigmented Moisture-Blocking Base for Concrete Floor Coating.

Supplier's details : Versatile Building Products
1900 Lakeway Dr Suite 500,
Lewisville, TX 75057
Tel.: (714) 829-2600
Toll Free: (800) 535-3325
Email:
contactus@versatile.net
Website: www.versatile.net

Emergency telephone number (with hours of operation) : InfoTrac: 1-800-535-5053
(8:00 a.m. – 5:00 p.m. PST)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
GHS label elements SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 2



Hazard pictograms :

Signal word : Warning

Hazard statements

- : H315 - Causes skin irritation.
- H317 - May cause an allergic skin reaction.
- H319 - Causes serious eye irritation.
- H351 - Suspected of causing cancer.

Precautionary statements

 KMK Regulatory Services	Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkgregservices.com www.askdrluc.com www.ghssmart.com	1/16
---	--	------



4195 Baja Beije Direct-To-Concrete A-Component

Section 2. Hazards identification

Prevention

- : P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P280 - Wear protective gloves, protective clothing and eye or face protection.
- P261 - Avoid breathing vapor.
- P264 - Wash thoroughly after handling.
- P272 - Contaminated work clothing must not be allowed out of the workplace.

Response

- : P308 + P313 - IF exposed or concerned: Get medical advice or attention.
- P362 + P364 - Take off contaminated clothing and wash it before reuse.
- P363 - Wash contaminated clothing before reuse.
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage

- : P405 - Store locked up.

Disposal

- : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

- : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Not available.

Ingredient name	%	CAS number
bis-[4-(2,3-Epoxypropoxy)phenyl]propane	≥25 - ≤50	1675-54-3
Titanium dioxide	≥10 - ≤25	13463-67-7
Limestone	≥10 - ≤25	1317-65-3
Acetone	≥3 - ≤5	67-64-1
[[[2-Ethylhexyl]oxy]methyl]oxirane	≥1 - ≤3	2461-15-6
1-Methoxy-2-propanol	≥1 - ≤3	107-98-2
Aluminium hydroxide	≥1 - ≤3	21645-51-2
Reaction Product: Bisphenol-A-(Epichlorhydrin); Epoxy Resin	≥0.3 - <1	25068-38-6
Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids	≥0.3 - <1	-
Ethylbenzene	≤0.3	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.

	Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com	2/16
---	---	-------------



4195 Baja Beije Direct-To-Concrete A-Component

Section 4. First aid measures

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards. Over-exposure

signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation watering redness

Inhalation : No known significant effects or critical hazards.

Skin contact : Adverse symptoms may include the following:
irritation redness

: No known significant effects or critical hazards.

Ingestion

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : No specific fire or explosion hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Methods and materials for containment and cleaning up



Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 15 to 35°C (59 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
bis-[4-(2,3-Epoxypropoxy)phenyl]propane Titanium dioxide	None. ACGIH TLV (United States, 3/2020). TWA: 10 mg/m ³ 8 hours.
Limestone	OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust
	OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction
	TWA: 15 mg/m ³ 8 hours. Form: Total dust NIOSH REL (United States, 10/2016). TWA: 5 mg/m ³ 10 hours. Form: Respirable fraction TWA: 10 mg/m ³ 10 hours. Form: Total



Acetone

ACGIH TLV (United States, 3/2019).

TWA: 250 ppm 8 hours.

STEL: 500 ppm 15 minutes.

NIOSH REL (United States, 10/2016).

TWA: 250 ppm 10 hours.

TWA: 590 mg/m³ 10 hours.

OSHA PEL (United States, 5/2018).

TWA: 1000 ppm 8 hours.

TWA: 2400 mg/m³ 8 hours.

None.

ACGIH TLV (United States, 3/2020).

[[[(2-Ethylhexyl)oxy]methyl]oxirane

1-Methoxy-2-propanol

Section 8. Exposure controls/personal protection

Aluminium hydroxide

Reaction Product: Bisphenol-A-(Epichlorhydrin); Epoxy Resin
Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids
Ethylbenzene

TWA: 50 ppm 8 hours.

TWA: 184 mg/m³ 8 hours.

STEL: 100 ppm 15 minutes.

STEL: 369 mg/m³ 15 minutes.

NIOSH REL (United States, 10/2016).

TWA: 100 ppm 10 hours.

TWA: 360 mg/m³ 10 hours.

STEL: 150 ppm 15 minutes.

STEL: 540 mg/m³ 15 minutes.

ACGIH TLV (United States, 3/2020).

TWA: 1 mg/m³ 8 hours. Form: Respirable fraction

None.

None.

ACGIH TLV (United States, 3/2020).

TWA: 20 ppm 8 hours.

NIOSH REL (United States, 10/2016).

TWA: 100 ppm 10 hours.

TWA: 435 mg/m³ 10 hours.

STEL: 125 ppm 15 minutes.

STEL: 545 mg/m³ 15 minutes.

OSHA PEL (United States, 5/2018).

TWA: 100 ppm 8 hours.

TWA: 435 mg/m³ 8 hours.

Appropriate engineering controls :

Environmental exposure controls :

Individual protection measures





Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Hygiene measures** :

Eye/face protection :

Skin protection

Hand protection :

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Section 9. Physical and chemical properties and safety characteristics



The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liquid. [Viscous. Opaque.] :
Color	: Light grey.
Odor	: Mild.
Odor threshold	: Not available.
pH	: Not available.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 260°C (500°F)
Flash point	: Closed cup: 252°C (485.6°F)
Evaporation rate	: Not available.
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Lower: 2.2% Upper: 13% (Acetone)
Vapor pressure	: 4.4 kPa (33 mm Hg) :
Relative vapor density	: Not available. : 1.462
Relative density	: Not available.
Solubility	: Not available.
Solubility in water	: Not available.
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	:

Ingredient name	°C	°F	Method
Acetaldehyde	175	347	DIN 51794
1,4-Dioxane	180	356	
Distillates (petroleum), hydrotreated light	>220	>428	
1-Methoxy-2-propanol	270	518	
Solvent naphtha (petroleum), light arom.	280 to 470	536 to 878	
2-Methoxy-1-methylethyl acetate	333	631.4	
2,6-Dimethylheptan-4-one	345	653	



Section 9. Physical and chemical properties and safety characteristics

Octamethylcyclotetrasiloxane	384 to 387	723.2 to 728.6	ASTM E 659
n-Butyl acetate	415	779	EU A.15
Cumene	424	795.2	
Ethylene oxide	429	804.2	
Formaldehyde	430	806	
Xylene	432	809.6	
Ethylbenzene	432.22	810	
Propylene oxide	449	840.2	EU A.15
Methanol	455	851	
Acetone	465	869	
Maleic Anhydride	477	890.6	
Toluene	480	896	
Benzene	498	928.4	
1,2,4-Trimethylbenzene	500	932	
Chloromethane	632	1169.6	

Decomposition temperature : Not available.

Viscosity : Dynamic: 400 to 600 mPa·s (400 to 600 cP) **Flow time (ISO 2431)** :

Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Section 11. Toxicological information

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid high temperatures.
Incompatible materials	: Reactive or incompatible with the following materials: strong bases and strong oxidizers.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.



Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-Epoxypropoxy)phenyl]propane	LD50 Dermal	Rabbit	20 g/kg	-
Acetone	LD50 Oral	Rat	5800 mg/kg	-
[[[2-Ethylhexyl)oxy)methyl]oxirane	LD50 Oral	Rat	7800 mg/kg	-
1-Methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-Epoxypropoxy)phenyl]propane	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Acetone	Eyes - Mild irritant	Rabbit	-	10 µL	-



Section 11. Toxicological information

1-Methoxy-2-propanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	395 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Mild irritant	Rabbit	-	100 mg	-
Reaction Product: BisphenolA-(Epichlorhydrin); Epoxy Resin	Skin - Moderate irritant	Rabbit	-	24 hours 500 µL	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-
Ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-

Sensitization There is no data available.

Mutagenicity There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP
bis-[4-(2,3-Epoxypropoxy)phenyl]propane	-	3	-
Titanium dioxide	-	2B	-
Ethylbenzene	-	2B	-

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Acetone	Category 3	-	Narcotic effects
1-Methoxy-2-propanol	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
------	----------	-------------------	---------------

Section 11. Toxicological information

Ethylbenzene	Category 2	-	hearing organs
--------------	------------	---	----------------

Aspiration hazard

Name	Result
Ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact : Causes serious eye irritation.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
 pain or irritation watering redness

Inhalation : No known significant effects or critical hazards.

Skin contact : Adverse symptoms may include the following:
 irritation redness
 : No known significant effects or critical hazards.

Ingestion

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : No known significant effects or critical hazards.
Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate effects : No known significant effects or critical hazards.
Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates



Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
bis-[4-(2,3-Epoxypropoxy)phenyl]propane	N/A	20000	N/A	N/A	N/A
Acetone	5800	N/A	N/A	N/A	N/A
[[[2-Ethylhexyl)oxy)methyl]oxirane	7800	N/A	N/A	N/A	N/A
1-Methoxy-2-propanol	6600	13000	N/A	N/A	N/A
Ethylbenzene	3500	N/A	N/A	11	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide Acetone	Acute LC50 >1000000 µg/L Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute EC50 7200000 µg/L Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 6000000 µg/L Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 6900 mg/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - Poecilia reticulata	96 hours
	Chronic NOEC 4.95 mg/L Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Daphnia magna Neonate	21 days
	Chronic NOEC 5 µg/L Marine water	Fish - Gasterosteus aculeatus Larvae	42 days
	Chronic NOEC 5 µg/L Marine water	Fish - Gasterosteus aculeatus Larvae	42 days
Ethylbenzene	Acute LC50 13.3 mg/L Marine water	Crustaceans - Artemia sp. Nauplii	48 hours
	Acute LC50 13.9 mg/L Fresh water	Daphnia - Daphnia magna Neonate	48 hours

Persistence and degradability

There is no data available.

Bioaccumulative potential



Section 12. Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Acetone	-0.23	-	low
1-Methoxy-2-propanol	<1	-	low
Reaction Product: BisphenolA-(Epichlorhydrin); Epoxy Resin	2.64 to 3.78	31	low
Ethylbenzene	3.6	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Acetone	67-64-1	Listed	U002



Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN3082	Not regulated.	Not regulated.
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Xylene)	-	-
Transport hazard class(es)	9  	-	-
Packing group	III	-	-
Environmental hazards	Yes.	No.	No.



4195 Baja Beije Direct-To-Concrete A-Component

Section 14. Transport information

AERG : 171

DOT-RQ Details

: Xylene

100 lbs / 45.4 kg [13.946 gal / 52.791 L]

Additional information

DOT Classification

: Non-bulk packages of this product are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by inland waterway. The marine pollutant mark is not required when transported on inland waterways in sizes of ≤5 L or ≤5 kg.

Reportable quantity 23970.5 lbs / 10882.6 kg [1966.4 gal / 7443.6 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

IATA

: The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments

: Not available.

Section 15. Regulatory information

U.S. Federal regulations

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I Substances

Clean Air Act Section 602 Class II Substances

DEA List I Chemicals



KMK Regulatory Services

Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) **16/20** www.kmkregservices.com
www.askdrluc.com www.ghssmart.com

Section 15. Regulatory information

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals)

SARA 302/304

: TSCA 4(a) final test rules:

Octamethylcyclotetrasiloxane

Clean Water Act (CWA) 307: Ethylbenzene; Benzene; Toluene; Chloromethane

Clean Water Act (CWA) 311: Xylene; Ethylbenzene; Maleic Anhydride; n-Butyl acetate;

Benzene; Toluene; Propylene oxide; Acetaldehyde; Formaldehyde

: Listed

TSCA 8(a) PAIR:

Octamethylcyclotetrasiloxane; 2-Methoxy-1-methylethyl acetate; Acetaldehyde

: Not listed

: Not listed

TSCA 8(a) CDR

Exempt/Partial

exemption: Not determined

: Not listed

: Listed

Composition/information on ingredients

Name	%	EHS	SARA 302 TPQ		SARA 304 RQ	
			(lbs)	(gallons)	(lbs)	(gallons)
Propylene oxide	≤0.00001	Yes.	10000	1444.3	100	14.4
Formaldehyde	≤0.00001	Yes.	500	73.9	100	14.8
Ethylene oxide	≤0.00001	Yes.	1000	-	10	-

SARA 304 RQ : 2222222222.2 lbs / 1008888888.9 kg [1822983912.6 gal / 6900744794

SARA 311/312

Classification

L]

: SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1

CARCINOGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification
bis-[4-(2,3-Epoxypropoxy)phenyl] propane	≥25 - ≤50	FLAMMABLE LIQUIDS - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
Acetone	≥3 - ≤5	FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
[[[2-Ethylhexyl]oxy]methyl] oxirane	≥1 - ≤3	SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1
1-Methoxy-2-propanol	≥1 - ≤3	FLAMMABLE LIQUIDS - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Reaction Product: Bisphenol-A(Epichlorhydrin); Epoxy Resin	≥0.3 - <1	SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids Ethylbenzene	≥0.3 - <1	SKIN SENSITIZATION - Category 1
	≤0.3	SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Ethylbenzene	100-41-4	≤0.3
Supplier notification	Ethylbenzene	100-41-4	≤0.3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed. [State](#)

regulations

Massachusetts

: The following components are listed: Titanium dioxide; Limestone; Acetone; 1-Methoxy-

2-propanol

New York

: The following components are listed: Acetone

New Jersey

: The following components are listed: Titanium dioxide; Limestone; Acetone; 1-Methoxy-

2-propanol; Ethylbenzene

Pennsylvania : The following components are listed: Titanium dioxide; Limestone; Acetone; 1-Methoxy2-propanol

California Prop. 65

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2	Calculation method



SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
 SKIN SENSITIZATION - Category 1
 CARCINOGENICITY - Category 2

Calculation method
 Calculation method
 Calculation method



4195 Baja Beije Direct-To-Concrete A-Component

Section 15. Regulatory information

⚠ WARNING: This product can expose you to chemicals including Benzene and Ethylene oxide, which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Titanium dioxide, Ethylbenzene, Crystalline silica, respirable powder, Cumene, Propylene oxide, Acetaldehyde, Formaldehyde and 1,4-Dioxane, which are known to the State of California to cause cancer, and Methanol, Toluene and Methyl chloride, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Ethylbenzene	Yes.	-
Crystalline silica, respirable powder	-	-
Cumene	-	-
Benzene	Yes.	Yes.
Methanol	-	Yes.
Toluene	-	Yes.
Propylene oxide	-	-
Acetaldehyde	Yes.	-
Formaldehyde	Yes.	-
Ethylene oxide	Yes.	Yes.
1,4-Dioxane	Yes.	-
Methyl chloride	-	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

United States (TSCA 8b) : All components are active or exempted.

Section 16. Other information

Procedure used to derive the classification



KMK Regulatory Services

Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) **19/20** www.kmkregservices.com
www.askdrluc.com www.ghssmart.com



Section 16. Other information

History	Date of issue/Date of revision	: 05/09/23
Date of previous issue	: Not applicable	
Version	: 1	
Prepared by	: KMK Regulatory Services Inc.	
Key to abbreviations	: ATE = Acute Toxicity Estimate	
	BCF = Bioconcentration Factor	
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals	
	IATA = International Air Transport Association	
	IBC = Intermediate Bulk Container	
	IMDG = International Maritime Dangerous Goods	
	LogPow = logarithm of the octanol/water partition coefficient	
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)	
	N/A = Not available	
	SGG = Segregation Group	
	UN = United Nations	

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

